

OPTICON

Windows CE



H15

Barcode laser scanner

Serial cradle



+ Related products



PHL7114

- Windows CE
- Barcode laser scanner
- Bluetooth, W-LAN (WiFi), GSM/GPRS, serial connector
- IP 54



OPH1004

- Batch Terminal
- Barcode laser scanner
- IrDA
- IP 54



PHL8112

- Windows CE
- Barcode laser scanner
- Bluetooth, W-LAN (WiFi), serial connector
- IP 65

Operation

- CPU: Intel PXA270 312Mhz
- O/S: Windows CE 5.0
- Software: Wordpad, Internet Explorer, Inbox, Active Sync, Messenger, Opticon scanner application, Accessories, Upgradeable via user accessible microSD
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

Memory

- FlashROM: 256 MB
- RAM: 64 MB
- Expansion: User accessible microSD + HC

Display

- Type: Graphic Transflective TFT with touch panel, 256K color with adjustable backlight
- Size: 2.4", 240 x 320 pixels
- Mode: Portrait

Operating indicators

- Visual: 2 LEDs (red/green)
- Non-visual: Buzzer

Operating keys

- Entry options: 25 keys total, 12 keys (alpha)numeric keypad, 4-way navigation keys, 4 function keys, 5 control keys, 1 power key, 2 hot keys, 1 scan key

Communication

- Bluetooth: Ver. 2.0, SPP, DUN, OPP, HID (only keyboard support), output power class 2
- W-LAN: 802.11b/g, CCK, TKIP, WEP, WPA, WPA2, EAP, LEAP, PEAP, AES, PSK (pre-shared, static, dynamic), Cisco CCX compatible Ver. 4

Power

- Rechargeable battery: Lithium-Ion 3.7V 1880mAh
- Operating time: Ca. 8 hours (backlight on, 1 scan + W-LAN connection / 5 sec)
- Charging method: Separate cradle CRD15 with spare battery bay
- Battery charging time: When battery in terminal ca. 3.5 hours charge, Separate battery ca. 5.5 hours

Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Vibrating mirror
- Scan rate: 100 scans/sec
- Reading pitch angle: -35 to 0°, 0 to +35°
- Reading skew angle: -50 to -8°, +8 to +50°
- Reading tilt angle: -20° to 0°, 0 to +20°
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.127 mm / 5 mil
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9, Code 39
60 - 640 mm / 2.36 - 25.20 in (1.00 mm / 39 mil),
40 - 410 mm / 1.57 - 16.14 in (0.5 mm / 20 mil),
40 - 250 mm / 1.57 - 9.84 in (0.25 mm / 10 mil),
40 - 140 mm / 1.57 - 5.51 in (0.15 mm / 6 mil),
50 - 110 mm / 1.97 - 4.33 in (0.127 mm / 5 mil)

Supported Symbologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Composite Codes, MicroPDF417, PDF417

Durability

- Temperature in operation: -10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 5 - 85% (non-condensing)
- Humidity in storage: 5 - 90% (non-condensing)
- Ambient light immunity: White 4,000 lx max, Fluorescent 4,000 lx max, Direct sun 80,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Protection rate: IP 54

Physical

- Dimensions (w x h x d):
57 x 164 x 28/24 mm / 2.24 x 6.46 x 1.10/0.94 in
- Weight body: Ca. 225 g / 7.9 oz (incl. battery)
- Case: Black

Regulatory & Safety

- Product compliance: CE incl. LVD, FCC, cUL, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

Enclosed items

- Standard battery Lithium-Ion 3.7V 1880mAh
- Hand strap
- Stylus

Sold separately

- CRD15 Cradle: Serial communication, charging

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM